

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 June 2005 (23.06.2005)


PCT

(10) International Publication Number  
**WO 2005/056974 A1**

- (51) International Patent Classification<sup>7</sup>: **E21B 19/00**, 19/07, E04H 17/26
- (21) International Application Number: PCT/IB2004/052588
- (22) International Filing Date: 29 November 2004 (29.11.2004)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (30) Priority Data:  
RM2003A000567  
10 December 2003 (10.12.2003) IT
- (71) Applicant and  
(72) Inventor: **LAPORTELLA, Pier Giorgio** [IT/TT]; Via Paolo V, 19, I-00167 Roma (IT).
- (74) Agents: **ROMANO, Giuseppe** et al.; Società Italiana Brevetti S.p.A., Piazza di Pietra 39, I-00186 Rome (IT).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: APPARATUS FOR THE AXIAL MOVEMENT OF PIPING OR THE LIKE



(57) Abstract: An apparatus (1) for the axial movement of piping (2) comprises a support frame (5), and a pair of hoisting elements (11,13) one thereof fixed to the frame (5) and one thereof movable, sliding on guides (12); the apparatus further comprises actuation means for the movement of a hoisting element, giving thereto a cyclic reciprocating motion along the guides (12) between a bottom dead center (BDC) and a top dead center (TDC); such a motion, in conjunction with the action of tightening means prearranged therefor, allow the axial movement of the piping.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*